

UltraStudio SDI



Get an attractive, portable and fully machined aluminum design that looks great on your desktop or on location shoots. UltraStudio SDI includes SDI capture and playback, as well as a built in HDMI output for affordable local monitoring using a low cost television as a broadcast monitor. It also includes genlock and RS-422 deck control. UltraStudio SDI powers from the USB 3.0 connection so it is an extremely easy to install and very portable solution.

\$395

Connections

SDI Video Input

1 x 10 bit SD/HD switchable.

SDI Video Output

1 x 10 bit SD/HD switchable.

HDMI Video Output

1 x HDMI type A connector

SDI Audio Input

8 Channels embedded in SD and HD.

SDI Audio Output

2 Channels embedded in SD and HD.

HDMI Audio Output

2 Channels embedded in SD and HD.

Sync Input

Blackburst in SD, 720p50, 720p59.94, 1080i50 and 1080i59.94 formats or Tri-Sync in any HD format.

Device Control


Sony™ compatible RS422 deck control ports. Serial ports TxRx direction reversible under software control.

Computer Interface

USB 3.0

Power

USB 3.0 Bus Powered.



Codecs

Supports: AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, XDCAM EX, XDCAM HD, XDCAM HD422, Uncompressed 8-bit 4:2:2, Uncompressed 10-bit 4:2:2.

Software



DaVinci Resolve



Fusion



Final Cut Pro X



Premiere Pro CC



Avid Media Composer



After Effects CC



Avid Pro Tools



Steinberg Cubase



Sony Vegas Pro



Photoshop CC

Other supported applications include: Corel VideoStudio Pro X4, Nuke - The Foundry, Avid Symphony, Avid News Cutter, CyberLink Power Director, MAGIX Video Pro X4, Vidcaster Pro & Studio & Broadcast, Uniplay, Playbox AirBox, CasparCG, Magicsoft CG, Steinberg Nuendo, Flash Media Encoder, Xsplit Broadcaster, Wirecast, Livestream Procaster, Imagine Communications Velocity & InfoCaster.

Video Standards

SD Format Support

525p23.98 NTSC, 525p29.97 NTSC,
625p25 PAL

HD Format Support

720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25, 1080p30
1080PsF23.98, 1080PsF24, 1080PsF25,
1080PsF29.97, 1080PsF30
1080i50, 1080i59.94, 1080i60

SDI Compliance

SMPTE 259M and SMPTE 292M.

SDI Metadata Support

VITC read for 3:2 pulldown removal. VANC capture and playback using up to 3 lines of video in file. HD RP188. Closed captioning.

Audio Sampling

Television standard sample rate of
48 kHz at 24 bit.

Video Sampling

4:2:2

Color Precision

10-bit

Color Space

REC 601, REC 709

HDMI Configuration

HDMI automatically configures to
connected display.

HDMI Resolution

Pixel for pixel HD resolution input to
connected device.

HDMI Color Precision

10 bit

Multiple Rate support

SDI and HDMI video connections are
switchable between standard
definition and high definition. SDI
switches between 270 Mb/s standard
definition SDI and 1.5 Gb/s HD-SDI.

Copy Protection

HDMI input is unable to capture from
copy protected HDMI sources. Always
confirm copyright ownership before
capture or distribution of content.

Processing

Colorspace Conversion

Hardware based real time.

HD Down Conversion

Software based down conversion during
video playback.

HD Up Conversion

Real time standard definition to
1080HD and 720HD during video
capture.

HD Cross Conversion

Real time 720HD to 1080HD during
video capture.

Real Time Effects

Premiere Pro CC Mercury Playback
Engine effects. Avid Media Composer
internal effects.

Operating Systems



Mac OS X 10.9 Mavericks,
Mac OS X 10.10 Yosemite,
Mac OS X 10.11 El Capitan
or later.




Windows 8.1 or
Windows 10.

Power Requirements

USB Bus Powered.

Physical Specifications



Environmental Specifications

Operating Temperature
5° to 40° C (32° to 104° F)

Storage Temperature
-20° to 45° C (-4° to 113° F)

Relative Humidity
0% to 90% non-condensing

What's Included

UltraStudio SDI
USB 3.0 cable
Software CD
Mounting Plate

Extras

Software Included

Media Express, Disk Speed Test, Blackmagic Control Panel and Blackmagic driver on Windows™.

Internal Software Upgrade

Firmware built into software driver. Loaded at system start or via updater software.

Physical Installation

Requires a computer with onboard USB 3.0, or a USB 3.0 PCI Express 2.0 card. Does not support USB 2.0 capture and playback. Please check the Support pages to see the full system requirements.

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller